

Pole Display

Key Features:

- Ergonomic design
- Four selectable command emulation modes supported
- EPSON DM-202 Emulation is supported in all models except PD-2100PP
- Mounting plate provided to attach to counter or to the bottom of the cash drawer
- Shock-absorbing base for PD-2100S/PD-2200
- Two adjustable viewing angles and selectable brightness
- Adjustable pole height. (PD-2100/2200 series)
- Display slides horizontally left and right, and rotates 360°. (PD-2100/2200 series)
- PD-2500 and PD2600 are fixed pole height
- PD22100/2200/2500: JIVA series touch terminal option
- PD2601: Hybrid POS HT series touch terminal option



| Specifications: | | | | |
|--------------------------------|---|---------------------------------------|--|---|
| Model | PD2100 | PD2200 | PD2500 | PD2601 |
| Number of Characters Displayed | 2 lines of 20 characters | | | |
| Character Format | 5 x 7 dots | | | |
| Character Size | 11.25mm (H) x 7.2mm (W) | | | 9.03mm(H) x 5.25mm(W) |
| Display Type | Green Vacuum Fluorescent Display (VFD) | Blue Vacuum Fluorescent Display (VFD) | | Green Vacuum Fluorescent Display (VFD) |
| Display Tilt Angle | Horizontal Slide (~100mm), Horizontal Rotation (~360°), Vertical Height (135mm), Viewing Angle (14.5°, 30°) | | | Three adjustable viewing angles: 15°, 30°, 45° degree |
| Display Swivel Range | N/A | | | 270° degree |
| Display Head Size | 260mm(W) x 70mm(H) x 60mm(D) | | | 196.6mm(W) x 58mm(H) x 28.2mm(D) |
| Emulation Modes | 4 modes | | | 6 modes |
| Overall Heights | 309~444mm | 291~426mm | 556mm above mounting plate | 270mm above Hybrid POS system |
| Base Size | 80mm(W) x 51mm (H) x 60mm (D) | 220mm (W) x 41mm (H) x 110mm (D) | 94mm (W) x 65.6mm (D) and 114mm (W) x 76mm (H) mount plate | N/A |
| Application | Mounting plate to attach base to counter or to the bottom of cash drawer | stand-alone base | Mounting plate to attach base to counter or to the bottom of cash drawer | Attach to Hybrid POS system only |
| Weight | 1.5 lbs | 1.5 lbs | 2.86 lbs | |
| Power Supply | Adaptor included | Adaptor optional | | 5V DC in COM or USB connector |
| Interface | Standard serial | Serial pass through | | Serial (RS232C) or USB |
| Operating Temperature | -20°C ~ +50°C | | -20°C ~ +40°C | 0°C ~ +40°C |
| Storage Temperature | -40°C ~ +80°C | | -20°C ~ +70°C | |
| Relative Humidity | Operating: 20% to 85% (non-condensing) Non-operating: 5% to 90% (non-condensing) | | | |
| Vibration Resistance | 4G max. | | | |
| Impact Resistance | 40G | | | |

POSIFLEX™

1280 San Luis Obispo Avenue
Hayward, California 94544 USA
tel : 510-429-7097
fax : 510-475-0982
e-mail : sales@posiflexusa.com
www.posiflexusa.com