# K2714 POS Keyboard

Unitech's K2714 POS Keyboard is your data entry solution for Point fo Sale, kiosks, banking and financial applications.

# **Enhance productivity**

To minimize costs generated by training and operating errors, we added 21 relengedable keys that support adding color, icons and text, reducing the learning time and costly typing errors. Furthermore, the K2714 ships with our Windows® based Keyboard Configuration Manager, which simplifies configuration and provides Data Editing functions to customize output. All this with a few clicks.

# **Compact and reliable**

The K2714 POS Keyboard features a rugged, spacesaving design ideal for a wide range of environments. It incorporates a built-in, dual-track Magnetic Stripe Reader, 104 keys including Windows<sup>®</sup> Start and Properties keys. Its spill resistant construction guarantees an extended life cycle.

## Features

- Rugged, durable design.
- Spill resistant.
- Small footprint.
- Built-in Magnetic Stripe Reader.
- Windows<sup>®</sup> compatible.
- Good read LED.
- 21 relegendable keys.



#### Layout

| Number of keys:    | 104                                  |
|--------------------|--------------------------------------|
| Key travel:        | 4.0 ± 0.3 mm                         |
| Switch type:       | Membrane with a life of 20 million   |
|                    | cycles                               |
| Layout:            | Qwerty                               |
| Relegendable keys: | 21                                   |
| Programmable:      | N/A                                  |
| Remappable:        | N/A                                  |
| Indicators:        | Num Lock, Caps Lock, Scroll Lock and |
|                    | Good Read LEDs                       |

#### Interface

MiniDIN (PS/2) DIN (IBM AT)

#### Environmental

Operating Temperature: 0° to 55° C Storage Temperature: -20° to 65° C Humidity: 10 to 95% RH non-condensing

#### Electrical

Source: Voltage:

Keyboard port +5V DC ± 5% @ 250 mA

#### Mechanical

Width: Depth: Height: Weight: 15.8" (400 mm ) 8.3" (210 mm) 1.7"(43 mm) 2.8 lbs. (1.68 kg)

# www.unitech-adc.com

#### Unitech America

3700 Industry Ave. No 103 Lakewood, CA 90712 U.S.A. Phone: 1-800-861-8648 Fax: 1-562-490-0320 www.unitech-adc.com sales@unitech-adc.com Unitech Europe Ringbaan Noord 91 5046 AA Tilburg The Netherlands Phone: +31-13-460-9292 Fax: +31-13-460-9293 unitech-europe@wxs.nl

### Unitech Electronics

3 Fl., No. 5, Alley 6, Lane 235 Pao Chiao Rd, Hsin-Tien City Taipei Hsien, Taiwan, R.O.C. Phone: +886-2-2918-2657 Fax: +886-2-2917-1474 aidcsales@unitech.com.tw

Specifications subject to change without notice. Copyright 2000 Unitech Electronics Co., Ltd.. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. Microsoft and Windows CE are registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners. U.S.A. (11/00)

