1517L
15-inch LCD

Touchscreen Monitor

Integrated Touch

Commercial Grade

HDMI

Product Overview

The Elo 1517L 15-inch standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look coupled with a retail-focused feature set makes it an attractive solution for commercial touchscreen monitor needs. The 1517L, offered in white or black, is well suited for point-of-sale, point-of-information, point-of-service, interactive signage and loyalty systems.

The touchscreen monitor offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Available touch technologies:
- TouchPro® PCAP
- AccuTouch® Resistive
- IntelliTouch® SAW

Customize with an integrated 3-track magnetic stripe reader (MSR)

Desktop, wall or VESA mounting

1517L 15-inch LCD Touchscreen Monitor

Specifications	
Model	1517L
Color	Black
Active Display Area	11.97" x 8.98" / 304.13 mm x 228.10 mm
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	15.0" / 381.0 mm
Aspect Ratio	4:3
Native (Optimal) Resolution	1024 x 768
Other Supported Resolutions	640 x 480 60Hz,75Hz; 720 x 400 70Hz; 800 x 600 56Hz, 60Hz,75Hz; 1024 x 768 60Hz,75Hz
Number of Colors	16.2 million
Number of Touches	IntelliTouch & AccuTouch: Single-touch TouchPro PCAP: 10-touch
Brightness (typical)	LCD Panel: 300 nits TouchPro PCAP: 270 nits AccuTouch: 240 nits IntelliTouch: 270 nits
Response Time – Total (typical)	23 msec
Viewing Angle (typical)	Horizontal: ± 80° or 160° total / Vertical: 70°/80° or 150° total
Contrast Ratio (typical)	800:1
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select, Power Settings: Auto Adjust, Brightness, Contrast, H-position, V-position, Clock, Phase, Color Temperature, OSD Timeout, OSD Language, Sharpness, Recall Defaults, Information Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
I/O Ports	VGA, HDMI, DC jack, AC jack, USB Type B, RS-232 (DB-9)
Video	Analog VGA on Female DB-15 connector Digital HDMI on Type A receptacle Input Video Horizontal Sync frequency range: 31.5 – 60KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor AC input power connector: IEC 60320 C6 Monitor AC input voltage specifications: 100-240VAC, 50/60Hz. Monitor DC input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter) Monitor DC input voltage specifications: 12VDC +/- 5%
Power Consumption (typical)	Monitor - ON: 10.5W; SLEEP: 1.40W; OFF: 0.3W
Dimensions	With Stand: 14.1" x 7.8" x 12.5" / 358 mm x 197 mm x 319 mm Without Stand (Bezel): 14.1" x 1.97" x 11.22" / 358 mm x 50 mm x 285 mm Without Stand (Zero-Bezel): 14.1" x 1.73" x 11.22" / 358 mm x 44.1 mm x 285 mm
Shipping Box Dimensions	19.2" x 9.1" x 19.1" / 487 mm x 231 mm x 485 mm
Weight	Unpackaged: 9.48 lbs / 4.3 kg; Packaged: 16.09 lbs / 7.3 kg
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit 3-hole threaded mounting on bottom of stand
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	Argentina S-mark; Australia RCM; Canada cUL, IC; China CCC; Europe CE, United Kingdom UKCA; Japan VCCI; Korea KCC, e-Standby; Mexico NOM; Taiwan BSMI Mark; United States UL, FCC; International CB; RoHS, China RoHS, WEEE
Warranty	3 years standard
Extended Warranty Options	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	1517L, Quick Install Guide, VGA Cable (DB-15 male to DB-15 male), Touch USB Cable (USB Type A plug to USB Type B plug), Power cable - IEC 60320-C5 to NA/EU plug, Stand Base assembly, Filler Plate, HDMI cable

Ordering Information

Part Number	Technology	Surface Treatment	Interface	Bezel
E523163	AccuTouch	Antiglare	Serial/USB	Yes
E144246	AccuTouch ZB	Antiglare	Serial/USB	No
E344758	IntelliTouch	Antiglare	Serial/USB	Yes
E829550	IntelliTouch ZB	Clear	Serial/USB	No
E273226	IntelliTouch ZB	Antiglare	Serial/USB	No
E596184	TouchPro PCAP	Antiglare	Serial/USB	No

Learn more about Elo at **EloTouch.com**.

Americas
Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)
Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific
Tel +86 (21) 3329 1385
Elo.Asia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2025 Elo Touch Solutions, Inc. All rights reserved. 25102AES00011