




2495L 23.8-inch LCD

Open-Frame Touchscreen



600 NITs



Wide Viewing Angle



3-Year Warranty

Product Overview

Elo's 2495L 23.8-inch interactive open frame delivers the sleek design the 90-Series is known for with outstanding brightness. At almost 3x brighter than the 2494L, the brilliant 2495L TouchPro® PCAP display offers edge-to-edge glass for ease of integration and up to 10 touches for a tablet-like experience. Elo's open frames can be mounted in landscape, portrait, and face-up orientations providing optimal flexibility for integrating in any table, kiosk, or cabinet design. Whether viewing straight on or at an angle, close-up or from a distance, our open frames offer what you need while maintaining optimal clarity and the viewing experience you want to deliver.

With proven Elo expertise and built-in reliability, the industrial-grade display provides outstanding image clarity and light transmissivity, as well as stable, drift-free operation for accurate touch responses. Elo's open frames offer the versatility needed for commercial kiosk applications from industrial automation and gaming to self-service and retail.

Enable Smarter Kiosks - Pair your open frame with the Elo Backpack™ and EloView® to create an affordable, scalable, single-architecture deployment

Elo's TouchPro PCAP offers:

- 10-touch capability that passes UL-62368, IK-07 impact testing and GLI ESD 27kV air / 8kV contact

- OSD enabled touch thru with up to 6mm of additional coverglass for increased durability & protection

Video Interfaces: HDMI, VGA & Display Port

2495L 23.8-inch Open-Frame Touch

Specifications	
Model	2495L
Color	Black
Active Display Area	20.75" x 11.67" / 527.04mm x 296.46mm
Diagonal	23.8"
Aspect Ratio	16:9
Dimensions	22.41" x 13.43" x 1.46" / 569.2mm x 341.1mm x 37mm
Native Resolution	1920x1080 50, 60Hz
Other Supported Resolutions	640x480 60Hz; 720x400 70Hz; 800x500, 60Hz; 800x600 56, 60Hz; 1024x768 60Hz; 1280x800 60Hz; 1280x1024 60Hz; 1366x768 60Hz, 60Hz RB; 1440x900 60Hz, 60Hz RB; 1680x1050 60Hz, 60Hz RB; 1920x1080 50, 60Hz
Number of Colors	16.7 million
Number of Touches	10-touch
Brightness (typical)	LCD panel: 600 nits; TouchPro PCAP: 540 nits
Response (typical)	14 msec
Viewing Angle	Horizontal: 89°/178°; Vertical: 89°/178°
Contrast Ratio	1000:1
On-Screen Display	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
I/O Ports	USB TypeB, RJ45 for OSD remote key, VGA, HDMI, DisplayPort, 12V D/C in
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of DisplayPort video input Input Video Horizontal Sync frequency range: 30 - 82KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth) Monitor input power signal specifications: 12VDC +/- 5% Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) barrel length) Adapter input voltage range: 100-240 VAC Input frequency: 50-60 Hz
Power Consumption	ON (Typical - 100% Brightness): 32.95 W SLEEP FROM PC (monitor + adapter): 0.71 W OFF (monitor + adapter): 0.2 W
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Weight	Unpackaged: 12.47 lbs / 5.65 kg; Packaged: 16.7 lbs / 7.57 kg
Shipping Dimensions	27.24" x 17.8" x 7.48" / 692mm x 452mm x 190mm
Mounting Options	200mm x 100mm VESA mount on rear of unit; Flush mount with included brackets
Warranty	3 years standard
MTBF	50,000 hours demonstrated
Agency Approvals	Australia RCM; Canada cUL, IC; China CCC; Europe CE, TUV; Japan VCCI; Korea KCC; Mexico CoC; Taiwan BSMI; United States UL, FCC; International CB; Russia EAC; RoHS, China RoHS, WEEE
Compliance	GLI 27 kV air / 8 kV contact ESD compliant; UL 62368 ball-drop compliant; IK07 impact compliant
What's in the Box	HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, QIG, Flush Mount Brackets with screws, EEI Label, Japan Class-B TM info sheet

Ordering Information

Model	Part Number	Part Description	Technology	Interface	Surface Treatment	Video Interface
2495L	E506980	ET2495L-2UWD-0-MT-ZB-NPB-G	TouchPro PCAP	USB 2.0	Clear	HDMI, VGA & DisplayPort

Extended Warranty Options

Part Number	Description
E898247	4 Year Warranty Coverage
E898449	5 Year Warranty Coverage
E898648	3 Year Warranty Coverage + AUR
E894921	4 Year Warranty Coverage + AUR
E895125	5 Year Warranty Coverage + AUR

Learn more about Elo at EloTouch.com.

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, the Elo Backpack, EloView and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2023 Elo Touch Solutions, Inc. All rights reserved. 23031AES00121

