

1745C

Rear Mount



**3000 Series
17\"/>**

SPECIFICATIONS

Model	1745C	
Case/Bezel color	Galvanized sheet metal enclosure, black plastic square kiosk bezel	
Display type	FST CRT	
Display size	17.0" diagonal	
Display area dimensions, nominal	Default	11.8" (300 mm) H x 8.9" (225 mm) V
Monitor dimensions	Width	19.1" (485 mm)
	Height	13.5" (343 mm)
	Depth	16.3" (413 mm)
Dimensional drawing number	MS500332 Rev A (available at www.elotouch.com)	
Highest recommended resolution	1024 x 768 at 85 Hz (PC)	
Resolution presets	1024 x 768 at 85 Hz	
	800 x 600 at 85 Hz	
	640 x 480 at 60 Hz	
Dot pitch, nominal	0.27 mm	
Video bandwidth	100 MHz	
Scanning frequency	Horizontal 30–70 kHz; vertical 50–160 Hz	
Input video format	Analog (no proprietary video card needed)	
Input video signal connector	Mini D-Sub 15-Pin (female)	
Power supply	100–240 VAC, 50/60 Hz	
Power dissipation	65 W typical, 75 W max.	
Temperature	Operating 5°C to 55°C; storage –20°C to 65°C	
Humidity	Operating 10% to 80%; storage 5% to 95%; noncondensing	
Weight (approx.)	Actual 44 lb (20 kg); shipping 52 lb (23.6 kg)	
Warranty	Monitor	2 years
	Touch technology	2 years iTouch
Other features	Multilingual OSD; ENERGY STAR; 2 stage DPMS; VESA DDC Plug and Play	

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch	Serial	Antireflective	E64636-000	FCC/ICES-03 Class B, UL/cUL (*Recognized component), TÜV-Bauart, CE, VCCI, C-Tick, MPR II, DHHS, Demko
iTouch	USB	Antireflective	C21634-000	FCC/ICES-03 Class B, UL/cUL (*Recognized component), TÜV-Bauart, CE, VCCI, C-Tick, MPR II, DHHS, Demko

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.

3000 Series
17" CRT Touchmonitor

