

IMAGETEAM™ 3870

Cordless Linear Imager



Features

Multiple Scanner Support - Each base unit supports up to nine scanners simultaneously. This increases productivity and flexibility without the added costs of additional bases and terminals.

Application Work Groups - Supports up to nine application work groups on a single base. This extremely powerful feature increases the number of jobs supported by a terminal, and allows you to easily adjust to changing workloads.

Broad Range Coverage - Scanner coverage of 31,400 square feet (2,919 square meters) increases mobility and productivity by allowing the scanner to be taken to the job, rather than taking the job to the scanner.

Eliminates Cables - Improves safety conditions by avoiding accidents and injury as a result of cables becoming entangled in equipment and machinery. Eliminates cable replacement costs.

Unique Charge Pack Design - Removable charge pack that is recharged simply by plugging into a wall outlet, then operates through the entire work day.

Rugged Design - Water and dust resistant to IP 54 rating.

State-of-the-Art Radio Technology - Two-way 2.4 GHz frequency hopping spread spectrum radio with forward error correction is robust against interference. Makes use of the license-free ISM band. Robust system delivers reliable and snappy, error-free communication.

The IMAGETEAM™ (IT)3870 cordless scanner addresses the needs of many applications. It is designed for tough industrial use, such as on loading docks, where shipping and receiving of materials requires the freedom to move around, and industry standards recommend the use of linear bar codes and PDF417 codes on shipping labels. The cordless scanner is also ideal for manufacturing applications, such as work-in-process, where safety may be an issue. Eliminating the cables prevents the cord from getting entangled in machinery and equipment, thus avoiding the chance of an accident. Other applications include interfacing to RF LAN based terminals mounted on forklift trucks, tool crib management, asset tracking, inventory control, and point-of-sale terminals.

The IT3870 joins a family of rugged and reliable cordless products, including the SCANTEAM® 2070 host interface base unit. The IT3870PDF is designed for aggressive reading performance on PDF417 and MicroPDF417. The IT3870HD reads high density bar codes with dimensions as small as 3 mil., while the IT3870LX reads 15 mil. codes out to 18 inches. All these configurations feature an IP 54 sealed-enclosure rating and the industry's best drop specification for cordless scanners.

The IT3870 features linear imaging technology in a cordless bar code reader. A bright, sharp aiming line and high-resolution imaging combine to deliver bar code reading performance that was previously only possible using a laser scanner.

The IT3870 offers many advantages over a laser scanner. Its aiming line is brighter than a standard laser. It scans and decodes 270 times per second, about seven times faster than a laser. It can read all common linear bar codes, plus PDF417 and MicroPDF417. Thanks to onboard Flash memory, the reader can be easily upgraded when new features and new symbologies become available.

Upgrade your image.



IMAGETEAM 3870 Specifications

Optical Performance

| | |
|------------------------------------|----------------------------|
| Illumination: | 630 nm Visible Red LED |
| Receiving Device: | 3648 element linear imager |
| Skew Angle: | ±30° |
| Pitch Angle: | ±15° |
| Horizontal Velocity: | 3 in. (7.6 cm) per second |
| Min. Reflective Difference: | 30% |
| Scan Rate: | 270 scans per second |

Mechanical/Electrical

| Dimensions | 3870 Scanner | 2070 Base |
|---------------------------|---|---|
| Weight: | 16 oz. (448 g) | 7.25 oz. (206 g) w/o cable |
| Height: | 8.5 in. (21.6 cm) | 1.4 in. (3.6 cm) |
| Power Requirements | | |
| Input Voltage: | 4 to 14 VDC | 4 to 14 VDC |
| Current Draw | | |
| Operating: | 425 mA (typical) while scanning | 325 mA (typical) @5 VDC |
| Standby: | 30 mA | NA |
| Environmental | | |
| Sealing: | IP 54 (Water and Dust Resistant) | IP 53 (Water and Dust Resistant) |
| Temperature | | |
| Operating: | 32° to 122°F (0° to 50°C) | -4 to 122°F (-20° to 50°C) |
| Storage: | -22° to 140°F (-30° to 60°C) | -40° to 158°F (-40° to 70°C) |
| Humidity: | 0 to 95%, non condensing | 0 to 95%, non condensing |
| Mechanical Shock: | Functional after 26 drops from 6 ft. (1.8 m) | Functional after 26 drops from 4 ft. (1.2 m) |

| | | |
|------------------------------|----------------------------------|----|
| Ambient Illumination: | 0-100,000 lux | NA |
| ESD Protection: | Functional after 15 kV discharge | |

Radio

| | |
|--------------------|--|
| Frequency: | 2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Spread Spectrum |
| Range: | 100 ft. (30 m) typical |
| Data Rates: | 1 Mbps |

Charge Pack

| | |
|-------------------------------------|---|
| | Nickel Metal Hydride (NiMH) battery |
| Input Voltage: | 120 V/240 V, 50 Hz/60 Hz |
| Capacity: | 1200 mAh |
| Number of Scans: | 18,000 |
| Expected Hours of Operation: | 25 hours @ 1 scan every 5 seconds |
| Charge Time at 120 Vac: | 6 hours for full charge from full discharge |

Symbologies

| | |
|-------------------------------|--|
| Symbologies Supported: | Codabar, Code 39, Code 128, ISBT 128, UPC/UPC-E, EAN/JAN, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 93, Code 11, ISBN, Telepen, and Reduced Space Symbology (RSS). IT3870PDF: PDF417, MicroPDF417, and EAN•UCC Composite Symbology. |
|-------------------------------|--|

Warranty

Three year factory warranty

Agency Conformance

Consult your HHP Customer Account Representative for specific country agency

| Electromagnetic Emissions/Immunity | Safety | RF Approvals |
|--|---|---|
| USA: UL listed, C22.2 No 950/UL 1950 Canada: SOR 88/475 Class B Europe: EN 55022 (CISPR22) Class B, EN 61000-3-2 & -3, ETS 300 826 Other: EMC 89/336/EEC, EN 50082-1:1992, IEC 801-2:1991, IEC 801-3:1984, IEC 801-4:1988 | USA: UL listed, C22.2 No 950/UL 1950 Canada: cUL Listed Europe: TUV Rheinland GS Licensed EN 60950 (IEC950) Australia: AS/NZS 3548 | USA: FCC Part 15.249 Canada: RSS 210 Europe: ETS 300 328 |

Worldwide Offices

Offices Serving North America
 Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 782 4263
 sales@hhp.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 782 4263
 sales@hhp.com

Offices Serving Europe, Middle East, and Africa
 Europe
 Tel: +31 (0) 40 29 01 600
 euro_sales@hhp.com
 United Kingdom
 Tel: +44 (0) 1 925 240055
 euro_sales@hhp.com
 Ireland
 Tel: +353 (0) 502 44007
 euro_sales@hhp.com

France
 Tel: +33 (0) 1 461 04111
 euro_sales@hhp.com
Germany
 Tel: +49 (0) 7 477 151377
 euro_sales@hhp.com
Spain
 Tel: +34 93 228 76 68
 euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim
 Hong Kong
 Tel: +852 2511 3050/2511 3132
 asia_sales@hhp.com
Japan
 Tel: +813 52127392
 asia_sales@hhp.com

Offices Serving Latin America
 Naples, Florida
 Tel: +1 239 263 7600
 la-sales@hhp.com
 S. o Paulo
 Tel: +55 11 5016 3454
 la-sales@hhp.com
 Rio De Janiero
 Tel: +55 21 2494 7060
 la-sales@hhp.com

Web Site Address www.hhp.com
 Hand Held Products, Inc. d/b/a HHP (IHHP) © 1999-2002. All rights reserved. Printed in the U.S.A.
 Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.