

Product Profile

- Lightweight, rugged and weather resistant
- Resilient high density polyethylene case
- Lithium-ion battery
- User downloadable character sets
- Works with Windows CE
- 4Mbits of flash can be updated
- Power saving sleep mode
- Intermec 782 Workboard



7 8 2 P R I N T E R W O R K B O A R D

Rugged and Affordable

The new Intermec 782 thermal and dot matrix printers are small, light durable units that can be used in even the most challenging delivery environment. Made especially to hold Intermec's 700 Series, the 782 offers exceptional clarity and versatility. These printers can quickly print both standard and bar coded receipts plus graphics such as captured signatures. Intermec printers have the features that maximize portability and minimize size along with the ability to withstand the rugged conditions of distribution applications. The printer's simple design makes paper loading easy and Lithium-ion batteries offer maximum power capacity while keeping weight to a minimum.

Reliable Quality

The reliable printer mechanism of the Intermec 782 enables use in the most challenging delivery environment. This durability does not come at the expense

of print quality, as the new 782 printer offers exceptional print clarity and the versatility of graphics capability for logos and even bar codes.

Power to Spare

The automatic power savings sleep mode and quick three hour recharge time along with the vehicle charger option creates the optimum application solution for a long service day.

782T Printer Workboard is Designed Especially for 700 Series

Designed specifically to hold the new Intermec 700 Series mobile computer, the 782 printer workboard offers a rugged one-piece solution. The 782T features a 40-column direct thermal printer. The printer workboard accommodates a hand strap, shoulder strap and is capable of being mounted in a vehicle. Durable in design, these workboards easily take the punishment of daily work environments.

Physical Characteristics**Length:** 29.01cm (11.42 in.)**Width:** 21.34cm (8.40 in.)**Height:** 6.68cm (2.63 in.)**Weight:** 800grams (28.22 ozs) without paper**Environment**

-20° to 50° C (-4° to 122° F)

Relative Humidity: 10% to 90% non-condensing**Drop Test:** 5 foot to concrete**Power Source****Type:** 7.2 v Lithium-ion 1800mAh (2) 3.8 V cells in series**Battery Life:** 300 Cycles with 80% capacity remaining**Battery:** Factory/Service Center replaceable**Recharging:** Nine hours to full charge using an vehicle charger Power adapter or standard AC power adapter.**Charge Jack:** 2.5 mm DC jack 12V – 15V**Print Specifications****Print Mechanism:** 384 dots across**Print Speed:** 1.83 in. per second**Fonts:** Hundreds of fonts available. 782T comes with seven (7) standard load fonts.**Printer Capabilities:** Characters, graphics and bar codes**Paper Medium:** 782T Thermal paper**Print Duration Per Charge:** Depended on usage and thermal printer engine.

An 8-hour shift is easily accomplished.

Hardware**Interface:** IrDA® RS-232: 6-position modular data jack/flash re-programmable**Card Reader:** Optional**Chargers:** AC wall charger; 12v vehicle charger**Regulatory Approvals**

FCC title 47, Part 15, Subpart B, Class B

EN55022 Class B

EN50082-1

IEC1000-3-2

IEC1000-3-3

**North America**

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada

7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

Europe/**Middle East & Africa**

Headquarters
 Reading International Business Park
 Basingstoke Road
 Reading RG2 6DD
 United Kingdom
 tel: 44.118.923.0800
 fax: 44.118.923.0801

Asia

Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86.10.5165.5922
 Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
 St. Leonards, NSW 2065
 Australia
 tel: 61.2.9330.4400
 fax: 61.2.9437.0204

South America & Mexico

Intermec South America Ltda.
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

OEM Sales

tel: 425.348.2762

Service and Support

800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
 611015-01D 12/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.