

Simple. Rugged. Reliable. ^{2t} And Now Wireless!

O'Neil Product Development, the world leader in rugged portable printers, continues its history of innovation by introducing its WLAN and WPAN printing solutions.



microFlash
Thermal Wireless Printer

^{2t}

Our worldwide customer base can now extend the reach of their enterprise networks by enabling frontline workers to print 2" wide receipts and labels at virtually any point of operation. Housed in an unbreakable polyethylene case, the microFlash 2t is light enough to be worn on a belt yet rugged enough to withstand multiple 6' drops to concrete. Designed for mobile printing applications in manufacturing, route accounting, distribution, transportation, and logistics, the microFlash 2t wireless printer delivers the performance and flexibility required by modern day supply chain operations.

Wireless!

Introducing WLAN & WPAN printing solutions.



Wireless MicroFlash 2t

Extend the reach of enterprise networks by enabling frontline workers to print 2" wide receipts and labels at virtually any point of operation.

microFlash

Thermal Wireless Printer

2t



PRODUCT DEVELOPMENT

8 Mason
Irvine, CA 92618, USA
949.458.0500 (tel)
949.458.0708 (fax)
www.oneilprinters.com
sales@oneillinc.com (e-mail)

EUROPEAN OFFICE

Witan Court
285 Upper Fourth Street
Witan Gate West
Central Milton Keynes
United Kingdom MK9 1EH
+44 1908 393300 (tel)
+44 1908 393400 (fax)
www.oneilprinters.com
sales@oneillinc.com (e-mail)

Simple. Rugged. Reliable. And Now Wireless.

Our wireless local area networking solution incorporates a user installable Cisco® PC Card (PCMCIA) which connects the microFlash 2t printer to a wireless network in ad hoc peer-to-peer mode or in infrastructure mode and complies with the IEEE 802.11b interoperability standards for direct sequence wireless LANs. When the printer is configured with the integrated Bluetooth™ module, mobile workers can realize all of the convenience, power efficiencies, and cost benefits of a wireless personal area network. As the first portable printer manufacturer to incorporate the Bluetooth protocol in flash memory, O'Neil Product Development has eliminated the need to return the microFlash 2t printer to the factory for costly software and hardware upgrades whenever the Bluetooth wireless specification changes.

Standard Features at a Glance

- WLAN or WPAN networking technologies
- Supports a wide variety of handheld computers from leading manufacturers
- Exceptional print quality (203 dpi resolution)
- Fonts, graphics and operating system stored in flash memory
- Supports international character sets and any Bitstream® bitmap font
- Increased label capacity through the use of linerless label stock (optional)
- Supports the printing of graphics, 1D and 2D bar codes, and signature capture
- Intelligent power management and programmable sleep mode for extended battery life
- Charging options include a low cost AC adapter or 12V vehicle cigarette lighter
- Optional Magnetic Stripe and Smart Card Reader

Specification Highlights **microFlash 2t Thermal Wireless Printer**

Physical Characteristics:	
Dimensions	7.37 in. x 5.52 in. x 2.42 in. 18.72 cm x 14.02 cm x 6.15 cm
Weight (with battery and paper roll):	39.0 oz. / 1,105.6 g
Drop Specification:	6ft. / 1.8m
Environment:	
Operating Temp	-20° C to 50° C / -4° F to 122° F
Storage Temp	-40° C to 70° C / -40° F to 158° F
Charging Temp	-10° C to 40° C / 14° F to 104° F
Relative Humidity	10% to 90% noncondensing
ESD Protection	8 kV Air, 4 kV Contact
Print Technology:	
Direct Thermal	1.85" (47mm) print width
Print Head Life	203.2 DPI, 8 dots/mm
Print Speed	5,000,000 dot lines Up to 2.5 inches per second
Fonts & Languages:	
Memory Capacity	Flash/RAM memory: 8 / 4 Mbit
Standard Fonts	5.5CPI, 7.2CPI, 10.2CPI, 10.7CPI, 18.5CPI, 20.4CPI, 22.6CPI
Int'l Characters	Arab-T, Arab-S, Arab-E, Asian-A, Asian-B, shiftJIS, Greek, OCR-A, OCR-B, Unicode subset including Thai and Latin
Bar Codes	Prints 1D and 2D bar codes
Graphics	Supports storage of graphics and logos in flash memory. Also supports transient, print once graphics
Power Source:	
Battery	User replaceable, off-the-shelf 6V Nickel Metal Hydride 2100mAh (DR10)
DC Input	12-15V, built-in spike and surge protection
Battery Characteristics:	
Type	6V Nickel Metal Hydride 2100mAh (DR10)
Endurance (802.11b)	Prints 3,834 inches on a single battery charge (639 6" receipts)
Endurance (Bluetooth)	Prints 4,217 inches on a single battery charge (703 6" receipts)
Battery Life	80% of original capacity after 300 cycles
Recharging	2-3 hours from AC Adapter or Cigarette Lighter Adapter
Communications:	
RS-232 Serial	Up to 115.2k baud
Wireless LAN	Cisco Aironet® 350 Series PC Card (PCMCIA)
Frequency Band	2.4 to 2.4897 GHz
Data Rates Supported	1, 2, 5.5, and 11 Mbps
Network Standard	IEEE 802.11b
Network Architecture Types	Infrastructure and ad hoc
Wireless Medium	Direct Sequence Spread Spectrum (DSSS)
Personal Area Network	Integrated Bluetooth module
Network Environment	Ad hoc or piconet network environments
Protocol	Supports version 1.1 of the Bluetooth standard (SIG certification pending)
Media:	
Roll Capacity	Thermal paper: 1,300" / 33m Linerless: 720" / 18.2m
Paper Width	2.25" / 57.2mm
Media Types	Direct thermal paper, Labels Linerless labels (optional)
Agency Approvals: FCC B, CE, C-Tick, E-Mark	
Warranty: 1 Year (including printer case)	
Optional Accessories:	
Swivel Belt Loop	
AC Adapter	
Cigarette Lighter Adapter	
DB9F Data Cable	
Magnetic Stripe / Smart Card Reader	
Specifications are subject to change without notice. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.	
Copyright 2003, O'Neil Product Development, Inc. Part Number: 110121-000 Rev. 1 Made in U.S.A.	